

Product Comparison

	Description	NSM 12	Real VNC 5.0.6 Personal
Platform Flexibility	Support for Windows 8.1/8/2012/7/2008/Vista/2003/XP. 32 & 64 Bit.	Υ	Υ
	Legacy support for Windows 2000 and earlier.	Υ	Υ
	Support for Mac/Linux/Chrome OS	YYY	YYN
	Remote control from Windows/Mac/Apple iOS/Android	YYYYY	YYYY
	Legacy support for Windows Mobile/CE/Pocket PC/Solaris	YYYY	NNNN
	Support for Terminal Server Clients	Υ	N
	64bit Support for Intel EM64/AMD64	YY	NN
	Support for Intel® Core™ vPro™ processors	Υ	N
	Optimised for Thin Client /Zero Client/Virtual Desktop environments	YYY	NNN
Mobile Remote Control from iOS/Android	Connect to remote PCs from iPad, iPod Touch, iPhone	YYY	YYY
	Connect to remote PCs from any Android tablet or smartphone (including Kindle Fire)	YY	YY
	Watch/share/control modes	YYY	NNN
	Thumbnail view of each connected PC (Multiple)	Υ	N
	Interact with multiple Clients simultaneously (Android only)	Υ	N
	Pinch, pan and zoom support in Remote Control	Υ	Υ
	Adjust Colour Depth on the fly	Υ	N
	Chat and message to remote device	YY	NN
	Real time hardware inventory of a remote Client	Υ	N
	Display Wireless status and battery strength for a connected Client (Android Only)	YY	NN
	One-click Ctrl+Alt+Del	Υ	Υ
	PIN Connect with Remote User	Υ	N
	Home screen widgets (Android only)	Υ	N
	Multi monitor support	Υ	N
	Compression to minimise data usage	Υ	N
	64, 128 or 256-bit encryption	Υ	\$
	Unique security keys	Υ	N
Chrome OS Support	Connect to any Chrome OS device (via HTTP) from Win/Mac or Mobile	YYY	YYY
	Thumbnail view of each connected Chrome device	Υ	N
	Watch/Share modes	YY	NN
	For real time instruction/demonstrations, 'show' Control screen to Chrome devices	Y	N
	Multi monitor support	Υ	N
	Chat and message	YY	NN
	Copy clipboard	Υ	N
	Help Requests – Chrome Clients can send requests for help to the Control	Υ	N
	PIN Connect	Υ	N
	User Acknowledgement – the Chrome Client authorises each inbound connection request	Y	N
Protocol Support	Connectivity over TCP/IP and HTTP protocols	YY	YY



Instant and Secure Remote Control

	Legacy support for IPX/NetBIOS	YY	NN
	Ability to connect to Clients on different protocols and connection types simultaneously	Υ	N
	PSTN/ISDN Support	Υ	N
Connection Options	Browse for Clients/Browse for Clients starting with xxx	YY	NN
	Quick Connect by Client Name/Username/Network Address/Host- name	YYYY	YNYY
	On Start-up connect to a specified Group/Client/Dial-up Network/In Specified view mode	YYYY	NNNN
	Option to allow Remote User to initiate connection to Control	Υ	N
	Allow multiple Controls to connect simultaneously	Υ	Υ
	Simplified connectivity through Firewalls (Internet Gateway)	Υ	N
	Secondary Gateway for redundancy	Υ	N
	Customer service based PIN Connect facility	Υ	N
Control User Interface	Quick View Toolbar/Launch Application Toolbar	YY	NN
	Interactive thumbnail view of each remote system	Υ	N
	Thumbnail Zoom facility for an expanded view of the remote system	Υ	N
	Display Remote Systems as Thumbnails/Mouse over Thumbnails for an expanded view of remote systems	YY	NN
	At Control provide Remote System Display Name/Description/Contact Details/Logged on Username/PCType	YYYYY	NNNN
	Auto-group remote Clients by platform/OS/enclosure type and geolocation	YYYY	NNNN
	Instant view of remote Client devices grouped by platform/OS/enclosure type	YYY	NNN
	Geolocation – real time display of remote Client location (Country/City/State)	Υ	N
	Create custom Client groups to reflect company structure	Υ	N
	Flexible quick switch display mode – thumbnails, client icons	Υ	N
Remote Deployment	Install components remotely using Windows Domain/IP address(es)	YY	YY
Integration	Use key functions within SMS/Active Directory/Windows Explorer	YYY	NNN
File Locations	Customisable Configuration File Locations	Υ	Υ
Remote Control	View Multiple Remote Systems Simultaneously	Υ	Υ
	Watch/Share/Control Modes	YYY	YYY
	View Full Screen/Scale to Fit	YY	YY
	Blank the Remote Systems Screen whilst still Viewing/Annotate Whilst Viewing	YY	NN
	Restrict Maximum Colour Depth/Optimize Colour Depth during View	YY	YY
	Scan Remote Systems one at a time/Many at a time	YY	NN
	Lock/View/Chat to Scanned Remote Systems	YYY	NNN
Audio Support	Audio Support between Remote System and Control.	Υ	N
Show Mode	Ability to Show Control Desktop to the Remote System	Υ	N
Print Capture	Redirect the Remote Systems Print output to Control	Υ	Υ
Communications	Chat Function One to One/One to Many/Interactive Whiteboard	YYY	YYN
	Ability to Send Message to Remote User(s)	Υ	N
	Ability for Remote Users to Request Help	Υ	N

Y = Feature included as standard, N = Feature not included, \$ = Feature available with additional cost/product

Disclaimer:



Instant and Secure Remote Control

Other Key Functions	Power On/Power Off Remote Systems over the LAN	YY	NN
	Ability to Logon/Logoff/Shutdown/Reboot the Remote System	YYYY	NNNN
	Capture an image of the Remote System's Desktop to a File	Υ	N
	Remotely start applications on a Remote System	Υ	N
	Launch a Command Prompt on your PC for the Remote System	Υ	N
	Launch a Registry Editor on your PC for the Remote System	Υ	N
	Transfer Clipboard contents between Remote System(s) and Control	Υ	Υ
	Record screen activity to a video "replay file" for training or security.	Υ	N
Inventory	Perform a Hardware Inventory of the Remote System	Υ	N
	Perform a Software Inventory of the Remote System	Υ	N
	Display/Verify Hotfixes Installed on the Remote System	YY	NN
	Display/Manage running Applications on the Remote System	YY	NN
	Display/Manage running Processes on the Remote System	YY	NN
	Display/Manage Services on the Remote System	YY	NN
	Display Battery Level Indicator/Wifi Signal Strength for Remote Mobile devices	YY	NN
	Remote user can generate a local inventory	Υ	N
File Transfer	Drag and Drop File(s) between Remote Systems and the Control One to One/One to Many	YY	YY
	Explicitly Allow or deny File Transfer access to drives, folders and or files	Υ	N
	Only transfer changed blocks of data within a file if it already exists - Delta File Transfer	Υ	N
	At Control specify file transfer priority when viewing	Υ	N
	'Live Folders' displayed for quick selection	Υ	N
Scripting	Scripting Language	Υ	N
	Script Scheduler to automate frequent tasks	Υ	N
Security	Authenticate connections using NT Authentication/Active Directory Authentication/Proprietarypassword	YYY	NNY
	Restrict connections to the Remote System by IP Address/IP Subnet/ IPX Address/IPX Network	YYYY	YYNN
	Secure Connections using Security Key/Use License Details as Security Key	YY	YN
	At Remote System allow Control to connect silently/Notify Remote User on connect	YY	YN
	On Disconnect Lock/Logoff/Restart Client on disconnect	YYY	YYN
	Protect access to Control Configuration using Proprietary Password	Υ	N
	Protect access to Remote System Configuration using NT Authentication/Proprietary password	YY	NN
	Option for all Remote Systems to use the same configuration file stored on a secure shared location	Y	N
	At Remote System require User Acknowledgement on Connection/ Display reason for connection at Remote System	YY	YN
	Restrict Gateway Access to specific users	Υ	N
Encryption	Encrypt all communications between Control and Remote System	Υ	Υ

Y = Feature included as standard, N = Feature not included, \$ = Feature available with additional cost/product

Instant and Secure Remote Control

	At Remote System force Controls to use encryption/force Controls to use specified encryption levelor higher	YY	YY
	256 bit AES Encryption or higher	Υ	Υ
User Profiling	Client side profiling of Control users (Enable/Disable Functionality)	Υ	Υ
	Profiling of Control by user (Enable/Disable Functionality)	Υ	N
	Create Desktop Shortcut to load specific Control profile	Υ	Υ
	Configure using Active Directory Group Policies	Υ	N
	Record Gateway Activity to Log File	Υ	N
	Record Screen Activity at Remote System/At Control/With Audio/ customisable location	YYYY	NNNN
	Record Activity to NT Event Log at Remote System	Υ	N
	Record Activity to Log File at Remote System/at Control/Customisable secure location	YYY	NNN
	Secure Log files on network using NT Security for Remote System/for Control	YY	NN
	Allow multiple Remote Systems to log activity to same file/Allow multiple Controls to log activity tosame file	YY	NN
	Secondary log file option to be used if first not accessible/reject connection if logging not possible	YY	NN
	Smartcard login supported	Υ	N
Remote Client (End User) Interface	One click Request Help facility	Υ	N
	PIN Connect – Client can create a unique PIN or enter a PIN provided by the Control for instant connection	Υ	N
	View a 'Replay File' – a previous screen recording of a remote control session	Υ	N
	Perform a local Hardware Inventory	Υ	N
	Perform a local Software Inventory	Υ	N
	Display/Verify Hotfixes installed on the local system	Υ	N
	Display/Manage running Applications on the local System	Υ	N
	Display/Manage running Processes on the local System	Υ	N
	Display/Manage Services on the local System	Υ	N